

Isolan AHT

Technical Data Sheet

Isolan AHT

Material Definition

Appearance: Milky white liquid

Solid content: 42.0 - 44.0 %

Brookfield Viscosity (25°C): Max 500 mPa.s

pH value: 8.0 - 9.0

Application

Isolan AHT is a self-crosslinking acrylic solution suitable for crafting transparent or tinted primers, as well as sealers adept at suppressing the seepage of stains. There's no need to incorporate zinc oxide in these mixes. Films produced with Isolan AHT feature a good sandability and impressive resistance against scratching.

Storage

The optimum storage and handling temperature range is 5 °C to 30 °C. The product must be protected from heat and frost in order to maintain viability. Containers must not be restocked after they have been opened. Properly stored, Isolan AHT is stable for at least 12 months after the shipment has left our warehouse.

Packaging

Isolan AHT is available in IBCs (1000kg each) and drums (210kg each). MoQ are 2 pallets with 8 drums each or 1 IBC.

Regulatory Information

EU REACH registered: Not applicable

Availability

- Americas (United States, Canada, South America)
- APAC (Asia-Pacific)
- ANZ (Australia, New Zealand)
- EU (European Union)
- PRC (People's Republic of China)
- UK (United Kingdom)

Disclaimer / Conditions



Revision: 2023-09-22 / 87b1

We strive to be accurate in all of our documentation. However, any information or advice is provided by us in good faith, without warranty or unlimited claim of fitness for a specific application. We sell to qualified industrial users only. The onus is on the product's user to research carefully and then to continually test the product and its application procedures within the context of its specific use. Use of our products and data requires diligence and care, and is within the sole responsibility of the user. Kautschuk-Group does not accept any liability for damages incurred. Our general [Terms and Conditions \(/info/toc\)](#) apply.

Stated storage and shelf life times are minimum guaranteed values for a period starting on the day of shipment. After this period has expired, the product requires additional quality control testing but may very well still be within specification. For more information, refer to our [Shelf Life Policy \(/info/shelflife\)](#).

For updates on product information, please check this web page regularly:

<https://kautschuk.com/products/textile/isolan-aht>

(<https://kautschuk.com/products/textile/isolan-aht>)

This page is also available in: **Deutsch**
(<https://de.kautschuk.com/products/textile/isolan-aht>), **Español**
(<https://es.kautschuk.com/products/textile/isolan-aht>), **Français**
(<https://fr.kautschuk.com/products/textile/isolan-aht>), **简体中文**
(<https://cn.kautschuk.com/products/textile/isolan-aht>), **Italiano**
(<https://it.kautschuk.com/products/textile/isolan-aht>), **Türkçe**
(<https://tr.kautschuk.com/products/textile/isolan-aht>), **日本語**
(<https://jp.kautschuk.com/products/textile/isolan-aht>).

© 2001-2023 Kautschuk Group · Isochem Limited · 340 Queen's Road, Central, · Hong Kong, SAR

For inquiries, contact: info@kautschuk.com (<mailto:info@kautschuk.com>)

[Status \(/status\)](#) · [Policies \(/info\)](#) · [Privacy \(/info/privacy\)](#) · [Terms \(/info/toc\)](#) · [Imprint \(/info/imprint\)](#)