

## Isobond<sup>®</sup> P - 100

**Chemical name:** Diphenyl (methylenedi-4,1-phenylene)dicarbamate

**CAS Number:** 101-65-5

**EINECS Number:** 202-963-4

## Material Definition

**Appearance:** Solid white to bright beige material

**Melting Point:** > 180 °C (capillary method)

**NCO-content:** < 0.1 % (Titration)

**Residual Humidity:** < 0.2 % (IR drying 80°C)

## Handling, Storage and Packaging

Stable for 24 months when stored in tightly closed original packing at temperatures between + 5°C and + 35°C without any exposure to sunlight.

## Regulatory Information

**EU REACH registered:** Yes

## Availability

- Americas (United States, Canada, South America)
- APAC (Asia-Pacific)
- ANZ (Australia, New Zealand)
- EU (European Union)
- PRC (People's Republic of China)
- UK (United Kingdom)

# Disclaimer / Conditions



Revision: 2023-07-14 / 398b

We strive to be accurate in all of our documentation. However, any information or advice is provided by us in good faith, without warranty or unlimited claim of fitness for a specific application. We sell to qualified industrial users only. The onus is on the product's user to research carefully and then to continually test the product and its application procedures within the context of its specific use. Use of our products and data requires diligence and care, and is within the sole responsibility of the user. Kautschuk-Group does not accept any liability for damages incurred. Our general [Terms and Conditions \(/info/toc\)](/info/toc) apply.

Stated storage and shelf life times are minimum guaranteed values for a period starting on the day of shipment. After this period has expired, the product requires additional quality control testing but may very well still be within specification. For more information, refer to our [Shelf Life Policy \(/info/shelflife\)](/info/shelflife).

For updates on product information, please check this web page regularly:  
<https://kautschuk.com/products/textile/isobond-p-100>  
(<https://kautschuk.com/products/textile/isobond-p-100>)

This page is also available in: **Deutsch**  
**(<https://de.kautschuk.com/products/textile/isobond-p-100>), Español**  
**(<https://es.kautschuk.com/products/textile/isobond-p-100>), Français**  
**(<https://fr.kautschuk.com/products/textile/isobond-p-100>), 简体中文**  
**(<https://cn.kautschuk.com/products/textile/isobond-p-100>), Italiano**  
**(<https://it.kautschuk.com/products/textile/isobond-p-100>), Türkçe**  
**(<https://tr.kautschuk.com/products/textile/isobond-p-100>), 日本語**  
**(<https://jp.kautschuk.com/products/textile/isobond-p-100>).**

© 2001-2024 Kautschuk Group · Isochem Limited · 340 Queen's Road,  
Central, · Hong Kong, SAR

For inquiries, contact: [info@kautschuk.com](mailto:info@kautschuk.com) (<mailto:info@kautschuk.com>)

**[Status \(/status\)](#) · [Policies \(/info\)](#) · [Privacy \(/info/privacy\)](#) · [Terms \(/info/toc\)](#) · [Imprint \(/info/imprint\)](#)**