

#### Isolan PCM

Isolan PCM is a dispersion of aliphatic polycarbonate ester-polyether polyurethane.

#### **Material Definition**

**Dispersion**: 60% solid content (low viscosity, water-based)

Viscosity @23°C: < 500 mPa\*s

pH value: 8 ±1

Volatile content: 40% ±2

Density @23°C: Approx. 1.1 g/cm<sup>3</sup>

# **Applications**

Isolan PCM is suitable for textile coating in various applications, such as outerwear, bags, workwear, and technical items.

Isolan PCM has a high solid content. It is suitable for applications that require excellent hydrolysis resistance and cross-linking properties. It is mechanically foamable and can be used to achieve good adhesion on various PVC surfaces. The end product has high scratch resistance, lightfastness, and resists mechanical bending.

## Storage

The optimum storage and handling temperature range is 5 °C to 30 °C. The product must be protected from heat and frost in order to maintain viability. Containers must not be re-stocked after they have been opened. Properly stored, Isolan PCM is stable for at least 12 months after the shipment has left our warehouse.

# Packaging

Isolan PCM is available in IBCs (1000kg each) and drums (210kg each). MoQ are 2 pallets with 8 drums each or 1 IBC.

## Regulatory Information

EU REACH registered: Not applicable

## **Availability**

- Americas (United States, Canada, South America)
- APAC (Asia-Pacific)
- ANZ (Australia, New Zealand)
- EU (European Union)
- PRC (People's Republic of China)
- UK (United Kingdom)

### **Disclaimer / Conditions**

Revision: 2023-11-15 / eb48



We strive to be accurate in all of our documentation. However, any information or advice is provided by us in good faith, without warranty or unlimited claim of fitness for a specific application. We sell to qualified industrial users only. The onus is on the product's user to research carefully and then to continually test the product and its application procedures within the context of its specific use. Use of our products and data requires diligance and care, and is within the sole responsibility of the user. Kautschuk-Group does not accept any liability for damages incurred. Our general <u>Terms and Conditions (/info/toc)</u> apply.

Stated storage and shelf life times are minimum guaranteed values for a period starting on the day of shipment. After this period has expired, the product requires additional quality control testing but may very well still be within specification. For more information, refer to our <u>Shelf Life Policy</u> (/info/shelflife).

For updates on product information, please check this web page regularly: https://kautschuk.com/products/textile/isolan-pcm (https://kautschuk.com/products/textile/isolan-pcm)

#### This page is also available in: **Deutsch**

(https://de.kautschuk.com/products/textile/isolan-pcm), Español (https://es.kautschuk.com/products/textile/isolan-pcm), Français (https://fr.kautschuk.com/products/textile/isolan-pcm), 简体中文 (https://cn.kautschuk.com/products/textile/isolan-pcm), Italiano (https://it.kautschuk.com/products/textile/isolan-pcm), Türkçe (https://tr.kautschuk.com/products/textile/isolan-pcm), 日本語 (https://jp.kautschuk.com/products/textile/isolan-pcm).

© 2001-2024 Kautschuk Group · Isochem Limited · 340 Queen's Road, Central, · Hong Kong, SAR

For inquiries, contact: info@kautschuk.com (mailto:info@kautschuk.com)

<u>Status (/status)</u> · <u>Policies (/info)</u> · <u>Privacy (/info/privacy)</u> · <u>Terms</u> (/info/toc) · <u>Imprint (/info/imprint)</u>