

Isodur RE

Chemical name: Triphenylmethane-4,4',4''-triisocyanate

CAS Number: 2422-91-5

EINECS Number: 219-351-8

Solvent: Ethylacetate

Material Definition

Appearance: Yellow-green, red brown to violet liquid. Product may contain flaky deposits.

NCO content of the solution: $9.3 \pm 0.2 \%$

Density: 0.98 g/cm^3

This product is identical in formulation to Desmodur RE and can be used as a drop-in replacement.

Notes

Kautschuk Group will be taking over as the REACH lead registrant in 2023.

Application

Isodur RE is a highly effective crosslinker for adhesives that are based on polyurethane, natural rubber and synthetic rubber (especially chloroprene rubber). It improves heat stability, hydrolysis resistance, and the resistance to greases, oils, and solvents.

Isodur RE offers an outstanding adhesion promotion for bonding a wide variety of materials such as PVC, rubber, EVA, or leather to metal and glass surfaces. This product is especially recommended where the bonds are exposed to considerable forces and stress or heat immediately after application. For instance, it is used for bonding shoe soles, including light-colored shoe materials.

Usage Information

After adding Isodur RE to a polyurethane- or rubber-based adhesive, the mixture must be used within its pot life. The pot life depends on the polymer content as well as on other ingredients like antioxidants, resins, plasticizers, solvents, etc. This pot life can vary from several hours to one day.

Handling, Storage, and Packaging

The processing and use of Isodur RE requires adequate technical and professional knowledge. Please consult safety data sheet and observe local safety regulations. The legal requirements prevailing in your country, especially in the avoidance of accidents, working hygiene and patent rights must be observed.

Isodur RE has to be stored in its sealed original containers at temperatures from 10 to 25°C. Properly stored it is stable for a minimum of six months. If it is stored or transported at low temperatures, crystalline deposits may form but they will re-dissolve at room temperature.

Available pack sizes for Isodur RE:

- 180 kg drums
- 50 kg drums
- 0.75kg Aluminium bottles

Regulatory Information

EU REACH registered: Yes

Silica dust (< 10µm): No

Substances of concern

Tin organic compounds present: **no**

Conflict minerals: **no**

3TG (section 1502 of Dodd-Frank Act): **no**

Cobalt/Mica 2017/821/EU: **no**

Chromium VI content: **no**

Chromium reducer: **no**

Biocide/s 528/2012/EU: **no**

Detergents 648/2004/EU: **no**

Nano materials (particle size <100nm): **no**

Fluorinated greenhouse gases 517/2014/EU: **no**

RoHS/GADSL/WEEE substances: **no**

Dual use 428/2009/EU: **no**

Rotterdam convention PIC 649/2012/EU: **no**

Montreal Protocol ODP 1005/2009/EU: **no**

Availability

- Americas (United States, Canada, South America)
- APAC (Asia-Pacific)
- ANZ (Australia, New Zealand)
- EU (European Union)
- PRC (People's Republic of China)
- UK (United Kingdom)

Disclaimer / Conditions



Revision: 2023-09-22 / 93b1

We strive to be accurate in all of our documentation. However, any information or advice is provided by us in good faith, without warranty or unlimited claim of fitness for a specific application. We sell to qualified industrial users only. The onus is on the product's user to research carefully and then to continually test the product and its application procedures within the context of its specific use. Use of our products and data requires diligence and care, and is within the sole responsibility of the user. Kautschuk Group does not accept any liability for damages incurred. Our general [Terms and Conditions \(/info/toc\)](#) apply.

Stated storage and shelf life times are minimum guaranteed values for a period starting on the day of shipment. After this period has expired, the product requires additional quality control testing but may very well still be within specification. For more information, refer to our [Shelf Life Policy \(/info/shelflife\)](#).

For updates on product information, please check this web page regularly:
<https://localhost/products/adhesives/isodur-re>
(<https://localhost/products/adhesives/isodur-re>)

This page is also available in: **Deutsch**
(<https://de.kautschuk.com/products/adhesives/isodur-re>), **Español**
(<https://es.kautschuk.com/products/adhesives/isodur-re>), **Français**
(<https://fr.kautschuk.com/products/adhesives/isodur-re>), **简体中文**
(<https://cn.kautschuk.com/products/adhesives/isodur-re>), **Italiano**
(<https://it.kautschuk.com/products/adhesives/isodur-re>), **Türkçe**
(<https://tr.kautschuk.com/products/adhesives/isodur-re>), **Polski**
(<https://pl.kautschuk.com/products/adhesives/isodur-re>), **日本語**
(<https://jp.kautschuk.com/products/adhesives/isodur-re>).

© 2001-2025 Kautschuk Group · Isochem Limited · 340 Queen's Road,
Central, · Hong Kong, SAR

For inquiries, contact: info@kautschuk.com (<mailto:info@kautschuk.com>)

[Status \(/status\)](#) · [Policies \(/info\)](#) · [Privacy \(/info/privacy\)](#) · [Terms \(/info/toc\)](#) · [Imprint \(/info/imprint\)](#)